

ECLS

Model SE200 Series

ELECTRONIC CONTROLLED SUZUKI SYSTEM BUTTONHOLER



Model SE200-S (for men's and ladies' wear)
SE200-J (for jeans)

Our technological innovation changes the imagination for the eyelet buttonhole sewing machine. The machine is very unique design, light weight and can be workable with simple operation by SUZUKI system that is electronic controlled. The needle bar, cloth clamp or knife action are very smoothly driven by built-in each high quality motors. It is not requested any special technique or compressed air for the machine. Machine maintenance, adjustment or noise will be reduced dramatically.

Feature & Technical Data

Selection of all functions are very easily by knob or dial, and you can see them through each illustrations on the control panel or other.



Control panel for error check, selection knob for C/B, C/A and sewing speed 1,000 ~ 2,000spm.



Compact control box



Foot switch for the clamp and start



Woolen material



Jeans material



Option: Hand-Switch(clamp & start)
(part No. SE-49K01A)

Technical Data

Specification/Model	SE200-S	SE200-J
Type of cloth clamp(standard)	Flat type	Wedge type
Stitch type	Single needle double-chain stitch	
Sewing speed	1,000 ~ 2,000spm.(adjustable)	
Type of buttonhole	Eyelet and Straight buttonhole	
Needle thread trimmer	Built-in	
Buttonhole length	14mm ~ 40mm	
Taper bar length	4mm ~ 9mm	
Stitch length	0.5mm ~ 1.5mm	
Stitch width	2.2mm ~ 3.2mm	
Knife/sewing selection	C/B, C/A, Sewing only and Cut only	
Needle bar and knife drive	Motor(built-in)	
Table quick feed drive	Motor(built-in)	
Cloth clamp lock/unlock	Motor(built-in)	
Needle system	Schmetz system 558 #90 ~ #120	
Power	AC100 ~ 120V or AC200 ~ 230V, 1-phase, 50/60Hz	
Machine weight	45kg(incl. motors and control box)	
Measurement	W300 x L500 x H460	

Machine color or specification may be changed without notice.

SUZUKI MACHINERY CO., LTD.

Head office

3-1, Kawaharada, Yamagata-Shi, Yamagata Pre.
990-0816 Japan

Tokyo office

Nanao Bldg. 3/F
5-5, 3-Chome, Taito, Taito-Ku, Tokyo 110-0016 Japan
TEL:81-3-5688-3260 FAX:81-3-5688-3261
<http://www.ecls.jp/> E-mail:suzuki@suzuki-ss.co.jp

For Distributor: